
Product data sheet

RING

article number 611.1230.28.02.83/30DA

manufacturer	bpe:LICHT GmbH & Co KG
mounting type	pendant luminaire
diameter (A)	1230mm
width (B)	60mm
height (C)	80mm
lamp	LED - CRI > 80
light output	20100lm
light output direct	10650lm
light output indirect	9450lm
colour temperature	3000K
light output	direct/indirect
attributes_light_distribution	symmetric
control	internal LED converter
converter	DALI
housing	extruded aluminium
surface	white
diffusor	satinised acrylic
power consumption	194W
suspension	Einzelseile
cable length	3000mm
shortable cable	yes
rated lifetime	L80/B10 50.000h bei 25°C
nominal voltage	220-240V - 50/60Hz
protection class	I
protection class	IP20





All technical data as well as weight and dimension information have been prepared carefully. Errors and omissions excepted.
Product pictures are exemplary and may deviate from the original. We reserve the right to make changes that serve progress.

© bpe:LICHT GmbH & Co. KG 2026/11/05

fon + 49 (0) 2932 90049-0
fax + 49 (0) 2932 90049-9
info@bpe-licht.de
www.bpe-licht.de

bpe:LICHT GmbH & Co. KG
gut nierhof 3 · 59757 arnsberg · voßwinkel
general manager: justin baulmann